

22849 Series Frame Anchor

- Consists of a nylon plug with countersunk head and a pozidriv screw, yellow zinc plated.
- Suitable for fixings on concrete, bricks and other high-density material.
- Material: Nylon (Polyamid 6)
- Temperature resistance: from -40° Celsius to +80° Celsius

22849 Series - 10mm Frame Anchor



| Item No. | Dimension Ø x L mm | Drill mm | Fixture Thickness mm | Pieces per | | Pull-out results in following building materials kN: | | |
|------------|-----------------------|-------------|-------------------------|------------|--------|--|-------------|----------------------------|
| | | | | Box | Carton | Concrete B25 | Bricks MZ20 | Sand lime full brick KSV20 |
| 2284910080 | 10 x 80 | 10 | 30 | 50 | 500 | 4.4 | 3.9 | 3.9 |
| 2284910100 | 10 x 100 | 10 | 50 | 50 | 500 | 4.4 | 3.9 | 3.9 |
| 2284910120 | 10 x 120 | 10 | 70 | 50 | 500 | 4.4 | 3.9 | 3.9 |
| 2284910140 | 10 x 140 | 10 | 90 | 50 | 500 | 4.4 | 3.9 | 3.9 |
| 2284910160 | 10 x 160 | 10 | 110 | 50 | 500 | 4.4 | 3.9 | 3.9 |
| 2284910180 | 10 x 180 | 10 | 130 | 50 | 500 | 4.4 | 3.9 | 3.9 |

Recommended security coefficient: 5